

Remote Eyes® Multi-View Client

Remote monitoring client supports 2048 cameras and 32 servers

Remote Eyes Multi-View Client brings the state of-the-art in video central station monitoring to security professionals. Using broadband connectivity to remote sites or LAN connectivity to multiple servers on premises, Multi-View users can be connected to and manage up to 2048 cameras on up to 32 servers simultaneously.



Multi-View's easy-to-use GUI makes even the most complex multi-site camera configuration usable for the average security professional. A simple tab interface allows the operator to quickly move from one server to the next. Composite camera layout views allow cameras of interest from multiple sites (e.g. all cash registers) to be displayed on a single panel for easy monitoring. A simple and graphical PTZ control panel allows quick and smooth control of camera motion, including joystick control. 2-way audio allows the operator to listen in on activity at the remote server and to issue voice commands to individuals at the remote site. Advanced camera viewing support allows viewing of up to 256 cameras at one time, using multiple monitors.

Multi-View is easy to set up on any Windows® 7 and up client workstation. Multi-View requires IP addressable WAN or LAN connectivity to the remote server(s).

Product Features

- > Windows® 7 and up compatible software
- > Compatible with Remote Eyes Enterprise Data Server™
- > Supports up to 4 monitors
- > Supports simultaneous connections to 32 Remote Eyes Servers
- > View up to 256 cameras at the same time
- > Supports up to 2048 remote cameras
- > Easy-to-use GUI allows rapid access to remote cameras per server
- > Full-screen display mode
- > Multiple persistent composite layout view allows cameras from multiple servers to be viewed in logical groups
- > High-speed remote clip playback and downloads
- > Sweep mode automatically rotates camera monitoring for central station operators
- > Motion alarms immediately highlighted to central station operator
- > Camera controls support remote PTZ cameras
- > Joystick PTZ interface
- > 2-way audio with any connected server
- > Broadband WAN or LAN connectivity

Product Specifications

Product Applications

- > Ideal client workstation environment for remote video monitoring
- > Multiple workstations can be used to scale to hundreds or thousands of cameras
- > Centralize guard monitoring “sweeps” of remote cameras
- > Manage multiple servers on single property using LAN connectivity

Minimum Client Workstation Requirements:

Intel® Pentium® processor; 2 GB RAM; 100 GB Hard Drive; 1024 x 768 display; Windows 7 or Higher



Odyssey Technologies, Inc.
7526 Connelley Drive, Suite A
Hanover, MD 21076
Tel: 888.291.6379
Fax: 301.362.9704
email: sales@remoteeyes.com
www.remoteeyes.com